



GF Adaptor in PP-H Serie: 910 PN10

Characteristics

Series: 910

Material: PP-H

Connection: Plastic welded end

Connection 2: External thread [BSPP]

Minimum medium temperature (continuous): 0 °C

Maximum medium temperature (continuous): 80 °C

Shape	External tube diameter of connection mm	Nominal inner diameter 2	Pressure rating	Article
Nipple	16	3/8"	PN10	10047600
Nipple	20	1/2"	PN10	10047601
Nipple	20	1/2"	PN10	11196237
Nipple	25	3/4"	PN10	10047602
Nipple	25	3/4"	PN10	11196239
Nipple	32	1"	PN10	10047603
Nipple	32	1"	PN10	11196240
Nipple	40	1.1/4"	PN10	11196242
Nipple	40	1.1/4"	PN10	10047604
Nipple	50	1.1/2"	PN10	10047605
Nipple	50	1.1/2"	PN10	11196253
Nipple	63	2"	PN10	10047606
Nipple	63	2"	PN10	11196254

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.