



GORE® Expanded PTFE sealing tape GORE 500

For industrial use only.

Not for use in food, drug, cosmetic, or medical device manufacturing, processing, or packaging operations.

Characteristics

Series: GORE

Type: 500

Material structure: Multidirectional expanded PTFE

Shape: Flat

Maximum temperature: 315 °C

Minimum temperature: -268 °C

Max. pressure: 40 bar

Suitable for medium: Natural gas, Acids, Chlorine
Water < 5% (7782-50-5), Air [compressed air], Fuels,
Refrigerants, Chlorine, gaseous (7782-50-5), Alkalis,
Biodiesel, Strong Alkalis, Strong Acids, Strong acids
[except hydrofluoric], Grease, Oil, Hydrocarbons,
Lubricant, Solvents, Cryogenic, Weak Alkalis, Weak
Acids

Application

- Recommended in: Chemical

Width mm	Thickness mm	Roller length m	Article
10	3	5	12327520
10	3	20	12327521
10	6	10	11185136
15	3	5	12327522
15	3	10	12327517
15	3	20	12327523
15	6	20	12327531
15	6	10	12327530
15	6	5	12327529
20	3	5	12327524
20	3	10	12327519
20	3	20	12327525
20	6	10	12327518
20	6	5	12327532
20	6	20	12327533
25	3	10	12327515
25	3	20	12327526
25	6	20	12327534
25	6	10	12327516
30	3	20	12327528
30	3	10	12327527
30	6	20	12327536
30	6	10	12327535

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.