

ERIKS Rubber flange gasket NBR 70 SUPERBA EN 1514-1 IBC



Characteristics

Series: NBR 70

Type: SUPERBA

Norm: EN 1514-1 IBC

Hardness (Sh A): 70 Sh A

Colour: Black

Temperature range: -20 / 80 °C

Max. pressure: 10 bar

Suitable for medium: Gases, Weak Alkalis,
Hydrocarbons, Air (compressed air), Fuel oil, Water,
Grease, Water (process water), Oil, Natural gas,
Lubricant, Fuels, Alkalis, Weak Acids

Number of inserts	Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Flange standard	Article
			mm	mm	mm		
0	DN10	PN6	39	18	3	EN 1092-1 RF	12252773
0	DN10	PN10/40	46	18	3	EN 1092-1 RF	12252774
0	DN15	PN6	44	22	3	EN 1092-1 RF	12252775
0	DN15	PN10/40	51	22	3	EN 1092-1 RF	12252776
0	DN20	PN6	54	27	3	EN 1092-1 RF	12252777
0	DN20	PN10/40	61	27	3	EN 1092-1 RF	12252778
0	DN25	PN6	64	34	3	EN 1092-1 RF	12252779
0	DN32	PN6	76	43	3	EN 1092-1 RF	12252781
0	DN32	PN10/40	82	43	3	EN 1092-1 RF	12252782
0	DN40	PN6	86	49	3	EN 1092-1 RF	12252783
0	DN40	PN10/40	92	49	3	EN 1092-1 RF	12252784
0	DN50	PN6	96	61	3	EN 1092-1 RF	12252785
0	DN50	PN10/40	107	61	3	EN 1092-1 RF	12252786
0	DN65	PN6	116	77	3	EN 1092-1 RF	12252787
0	DN65	PN10/40	127	77	3	EN 1092-1 RF	12252788
0	DN80	PN6	132	89	3	EN 1092-1 RF	12252789
0	DN80	PN10/40	142	89	3	EN 1092-1 RF	12252790
0	DN100	PN6	152	115	3	EN 1092-1 RF	12252791
0	DN125	PN6	182	141	3	EN 1092-1 RF	12252794
0	DN125	PN10/16	192	141	3	EN 1092-1 RF	12252795
0	DN125	PN25/40	194	141	3	EN 1092-1 RF	12252796
0	DN150	PN6	207	169	3	EN 1092-1 RF	12252797
0	DN150	PN10/16	218	169	3	EN 1092-1 RF	12252798
0	DN200	PN6	262	220	3	EN 1092-1 RF	12252799
0	DN200	PN10/16	273	220	3	EN 1092-1 RF	12252800
0	DN250	PN6	317	273	3	EN 1092-1 RF	12252801
0	DN250	PN10	328	273	3	EN 1092-1 RF	12252802
0	DN250	PN16	329	273	3	EN 1092-1 RF	12252803
0	DN300	PN6	373	324	3	EN 1092-1 RF	12252804
0	DN300	PN10	378	324	3	EN 1092-1 RF	12252805
0	DN300	PN16	384	324	3	EN 1092-1 RF	12252806
0	DN350	PN6	423	356	3	EN 1092-1 RF	12252807
0	DN350	PN10	438	356	3	EN 1092-1 RF	12252808
0	DN350	PN16	444	356	3	EN 1092-1 RF	12252809
0	DN400	PN6	473	407	3	EN 1092-1 RF	12252810
0	DN400	PN10	489	407	3	EN 1092-1 RF	12252811

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of inserts	Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Flange standard	Article
0	DN400	PN16	495	407	3	EN 1092-1 RF	12252812
0	DN500	PN6	578	508	3	EN 1092-1 RF	12252813
0	DN500	PN10	594	508	3	EN 1092-1 RF	12252814
0	DN500	PN16	617	508	3	EN 1092-1 RF	12252815
0	DN600	PN6	679	610	3	EN 1092-1 RF	12252816
0	DN600	PN10	695	610	3	EN 1092-1 RF	12252817
0	DN600	PN16	734	610	3	EN 1092-1 RF	12252818

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.