

REINZ Fibre flange gasket AFM 34 EN 12560-ISR



Characteristics

Series: AFM
Type: 34
Norm: EN 12560-ISR
With Inner eyelet: No
Fibre type: Aramid
Anti sticking layer: Yes
Temperature range: -50 / 250 °C
Max. pressure: 150 bar

Characteristics [2]

Suitable for medium: Fuels, Low pressure steam, Solvents, Oil, Air (compressed air), Chlorine, gaseous (7782-50-5), Natural gas, Lubricant, Chlorine Water < 5% (7782-50-5), Grease
Approval according to: BS6755, GL, API 6FB, HTB, DIN30653, TA-Luft, BAM, DVGW, BS7531 Grade X

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Flange standard	Article
		mm	mm	mm		
1"	300/900lbs	51	33	2	ASME B16.5	11515335
1.1/2"	300/900lbs	73	49	2	ASME B16.5	11515336
2"	300/900lbs	92	61	2	ASME B16.5	11324456
3"	300/900lbs	127	89	2	ASME B16.5	11324460
4"	300/900lbs	157	115	2	ASME B16.5	11324433
6"	300/900lbs	216	168	2	ASME B16.5	11333797

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.