

## FRENZELIT Fibre sealing sheet NOVAPRESS UNIVERSAL

### Characteristics

**Series:** NOVAPRESS

**Type:** UNIVERSAL

**Fibre type:** Aramid


**Anti sticking layer:** Yes

**Temperature range:** -100 / 200 °C

**Max. pressure:** 100 bar

### Characteristics [2]

**Suitable for medium:** Potable water, Biodiesel, Natural gas, Grease, Low pressure steam, Oil, Food & Beverages, Air (compressed air), Weak Alkalis, Weak Acids, Lubricant, Solvents, Refrigerants, Fuels  
**Approval according to:** Blow out VDI2200, DVGW, UBA Elastomerleitlinie, DVGW W270, EC1935/2004, TA-Luft, GL, BS7531 Grade X, WRAS, BAM



Thickness mm	Length mm	Width mm	Article
0.3	1500	1500	10017358
0.5	1500	1500	10017359
0.75	1500	1500	12560395
1	1500	1500	10017360
1.5	1500	1500	10017361
2	1500	1500	10017362
3	1500	1500	10017363
4	1500	1500	10017364
5	1500	1500	10017365

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.