

## SGL Carbon Graphite sealing sheet SIGRAFLEX ANTISTICK

### Characteristics

**Series:** SIGRAFLEX

**Type:** ANTISTICK

**Graphite purity:** ≥98 %

**Ash content %:** ≤2 %

**Insert material:** RVS 316 L [1.4404]

**Insert type:** Tanged

**Number of inserts:** 1

**Temperature range:** -200 / 450 °C

**Max. pressure:** 100 bar

### Characteristics [2]

**Suitable for medium:** Lubricant, Weak Alkalis, Oil, Grease, Natural gas, Hydrocarbons, Biodiesel, Weak Acids, Food & Beverages, Chlorine Water < 5% [7782-50-5], Solvents, Low pressure steam, Air [compressed air], Refrigerants, Fuels, Cryogenic, Chlorine, gaseous [7782-50-5]



Thickness mm	Length mm	Width mm	Article
1.6	1500	1000	12760513
2	1000	1000	10068516
3	1000	1000	10068517

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.