

FRENZELIT Graphite sealing sheet NOVAPHIT SSTC XP

Characteristics

Series: NOVAPHIT

Type: SSTC XP

Graphite purity: >99 %

Ash content %:

Insert material: RVS 316 L [1.4404]

Insert type: Expanded mesh

Number of inserts: 1

Temperature range: -200 / 450 °C

Max. pressure: 250 bar

Characteristics [2]

Suitable for medium: Cryogenic, Fuels, Air (compressed air), Chlorine Water < 5% [7782-50-5], Weak Alkalis, Refrigerants, Solvents, Food & Beverages, Low pressure steam, Lubricant, Oil, Hydrocarbons, Chlorine, gaseous [7782-50-5], Biodiesel, Weak Acids, Natural gas, Grease

Approval according to: FIRE-SAFE ISO 10497, BAM, API 6FB, DVGW, EC1935/2004

Thickness mm	Length mm	Width mm	Article
1	1500	1500	12443147
1.5	1500	1500	12443149
2	1500	1500	12443150
3	1500	1500	12443151

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.