



LEADER PTFE sealing sheet CLIPPERLON 2100

Characteristics

Series: CLIPPERLON

Type: 2100

Material structure: PTFE, modified

Max. temperature: 240 °C

Minimum temperature: -240 °C

Max. pressure: 85 bar

Suitable for medium: Weak Alkalis, Air (compressed air), Alkalis, Hydrocarbons, Solvents, Food & Beverages, Low pressure steam, Acids, Chlorine, gaseous [7782-50-5], Chlorine Water < 5% [7782-50-5], Strong acids (except hydrofluoric), Cryogenic, Weak Acids, Refrigerants

Approval according to: EC1935 [10/2011], FDA 21 CFR 177.1550, Blow out VDI2200, TA-Luft

Marking: Printed

Application

- Recommended in: Chemical

| Thickness mm | Length mm | Width mm | Article |
|-----------------|--------------|-------------|----------|
| 1 | 1500 | 1500 | 11917136 |
| 1.5 | 1500 | 1500 | 11917137 |
| 2 | 1500 | 1500 | 11917138 |
| 3 | 1500 | 1500 | 11917139 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.