

ERIKS PTFE flange gasket TEFMET EN 1514-1



Characteristics

Series: TEFMET

Norm: EN 1514-1 IBC

Material structure: PTFE, pure, virginal

Marking: Unprinted

Insert material: SS 304 [1.4301]

Temperature range: -100 / 250 °C

Max. pressure: 40 bar

Suitable for medium: Air [compressed air]

Application

- Recommended in: Chemical

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	2.5	10001572
DN15	PN10/40	51	22	2.5	10001573
DN20	PN10/40	61	27	2.5	10001574
DN25	PN10/40	71	34	2.5	10001575
DN32	PN10/40	82	43	2.5	10001576
DN40	PN10/40	92	49	2.5	10001577
DN50	PN10/40	107	61	2.5	10001578
DN65	PN10/40	127	77	2.5	10001579
DN80	PN10/40	142	89	2.5	10001580
DN100	PN10/16	162	115	2.5	10001581
DN100	PN25/40	168	115	2.5	10001589
DN125	PN10/16	192	141	2.5	10001582
DN125	PN25/40	194	141	2.5	11215650
DN150	PN10/16	218	169	2.5	10001583
DN150	PN25/40	224	169	2.5	10001590
DN200	PN40	290	220	2.5	11215703
DN200	PN10/16	273	220	2.5	10001584
DN250	PN10	328	273	2.5	10001585
DN300	PN10	378	324	2.5	10001586
DN400	PN10	489	407	2.5	10001587
DN500	PN10	594	508	2.5	10001588

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.