


ERIKS PTFE flange gasket FIRECHEM EN 1514-1



Characteristics

Series: FIRECHEM

Norm: EN 1514-1 IBC

Material structure: PTFE expanded

Marking: Printed

Temperature range: -200 / 260 °C

Max. pressure: 100 bar

Suitable for medium: Refrigerants, Acids, Chlorine, gaseous [7782-50-5], Alkalis, Cryogenic, Chlorine Water < 5% [7782-50-5], Strong acids (except hydrofluoric), Strong Alkalis, Solvents, Hydrocarbons, Air [compressed air], Weak Acids, Weak Alkalis, Low pressure steam

Approval according to: FIRE-SAFE ISO 10497

Application

- Recommended in: Chemical

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN15	PN10/40	51	22	3	11443205
DN20	PN10/40	61	27	3	11443206
DN25	PN10/40	71	34	3	11412906
DN32	PN10/40	82	43	3	11443207
DN40	PN10/40	92	49	3	11443208
DN50	PN10/40	107	61	3	11412908
DN65	PN10/40	127	77	3	11443209
DN80	PN10/40	142	89	3	11443210
DN100	PN10/16	162	115	3	11443211
DN100	PN25/40	168	115	3	11443212
DN125	PN25/40	194	141	3	11443214
DN125	PN10/16	192	141	3	11443213
DN150	PN10/16	218	169	3	11443215
DN150	PN25/40	224	169	3	11412909
DN200	PN25	284	220	3	11443217
DN200	PN40	290	220	3	11443218
DN200	PN10/16	273	220	3	11443216
DN250	PN25	340	273	3	11443221
DN250	PN16	329	273	3	11443220
DN250	PN40	352	273	3	11443222
DN250	PN10	328	273	3	11443219
DN300	PN10	378	324	3	11879442

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.