



BLICKLE Flanged wheel, series SPK

Cast iron flanged wheel. Tyre/running tread: Made of steel. Color: silver, Rim/wheel centre: - Color: silver, Shore: 180 - 220 HB. Oil-resistant. Operating temperature: -100° C up to +600° C, load capacity reduction of 50% at +600° C. A temperature-specific grease must be regularly applied. The indicated load capacities refer to the following rail profiles acc. to DIN 536 (crane rail standard): SPK 50G to SPK 200G, SPK 250G: A45.

Characteristics

Series: SPK

Type: SPK 100K

Wheel model	Tread material	Diameter	Width	Bearing weight	Bearing	Shaft diameter	Hub length	Temperature range	Article
		mm	mm	kg		mm	mm	°C	
Flanged wheel	Cast iron	50	32	400	Slide bearing	15	32	-100 / 600	10016468
Flanged wheel	Cast iron	75	40	700	Ball bearing	20	47	-25 / 120	10016533
Flanged wheel	Cast iron	100	46	800	Slide bearing	20	52	-100 / 600	11348961
Flanged wheel	Cast iron	100	46	800	Ball bearing	20	52	-25 / 120	10016537
Flanged wheel	Cast iron	125	46	900	Ball bearing	20	52	-25 / 120	11137964
Flanged wheel	Cast iron	125	46	900	Slide bearing	20	52	-100 / 600	12443356
Flanged wheel	Cast iron	150	46	1000	Ball bearing	20	52	-25 / 120	11040293
Flanged wheel	Cast iron	150	46	1000	Slide bearing	20	52	-100 / 600	11240501
Flanged wheel	Cast iron	180	46	1200	Slide bearing	30	52	-100 / 600	11071542
Flanged wheel	Cast iron	200	53	1500	Ball bearing	25	60	-25 / 120	11127143
Flanged wheel	Cast iron	200	53	1500	Slide bearing	30	60	-100 / 600	12173969
Flanged wheel	Cast iron	250	65	2500	Slide bearing	40	70	-100 / 600	12547939
Flanged wheel	Cast iron	250	65	2500	Ball bearing	30	70	-25 / 120	12547940

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.