



BLICKLE Wheel, series V

Wheel with standard solid rubber tyres, with pressed steel rim, reinforced design. Tyre/running tread: Made of standard solid rubber. Color: black, Rim/wheel centre: Pressed steel rim with tubular steel hub, bolted, zinc-plated, blue,-passivated, Cr6-free. Color: blue passivated, Shore: 80° Shore A. Chemical resistance to many aggressive substances, except oils. Operating temperature: -25° C to +80° C. At ambient temperatures above +60° C the load capacity is reduced. Maintenance-free under standard conditions.

Characteristics

Series: V

Type: V 100/15R

Wheel model	Tread material	Diameter	Width	Bearing weight	Bearing	Shaft diameter	Hub length	Temperature range	Article
		mm	mm	kg		mm	mm	°C	
Wheel	Gummi	100	30	70	Needle roller bearing	15	45	-25 / 80	10016354
Wheel	Gummi	160	40	135	Needle roller bearing	20	60	-25 / 80	10016357
Wheel	Rubber	80	25	50	Needle roller bearing	12	35	-25 / 80	10016353
Wheel	Rubber	125	37.5	100	Needle roller bearing	15	45	-25 / 80	10016355
Wheel	Rubber	140	37.5	115	Needle roller bearing	15	45	-25 / 80	12548053
Wheel	Rubber	140	37.5	115	Needle roller bearing	15	45	-25 / 80	10016356
Wheel	Rubber	180	50	170	Needle roller bearing	20	60	-25 / 80	12548059
Wheel	Rubber	180	50	170	Needle roller bearing	20	60	-25 / 80	10016358
Wheel	Rubber	200	50	205	Needle roller bearing	20	60	-25 / 80	10016359
Wheel	Rubber	200	50	205	Ball bearing	20	60	-25 / 80	12548062
Wheel	Rubber	200	65	225	Needle roller bearing	20	60	-25 / 80	12405735
Wheel	Rubber	250	60	295	Ball bearing	25	65	-25 / 80	11081201
Wheel	Rubber	250	60	295	Needle roller bearing	25	65	-25 / 80	10016360
Wheel	Rubber	250	75	320	Needle roller bearing	25	65	-25 / 80	12548076
Wheel	Rubber	280	70	385	Needle roller bearing	25	75	-25 / 80	10016361
Wheel	Rubber	300	60	700	Slide bearing	30	55	-25 / 80	12548081
Wheel	Rubber	400	75	300	Slide bearing	25	90	-25 / 80	11066853
Wheel	Rubber	400	80	475	Needle roller bearing	25	90	-25 / 80	11429463

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.