



GRUNDFOS Submersible pump Series: EF - Vuilwater pomp - gietijzer - 30 mm vrije doorgang

Characteristics

Series: EF

Connection: Internal thread (BSPP)

Material pump casing: Cast iron

Material quality: EN-JL1030

Insulation class acc. to IEC: F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m ³ /h	m		m	rpm	A		mm	
32400	32.4	10	1 x 230V AC	10	2920	4.8	2" (50)	494	23499049
32400	32.4	10	1 x 230V AC	10	2920	4.8	2" (50)	494	23499047
32796	32.8	10	3 x 400-415V AC	10	2920	2.3	2" (50)	494	23499050
32796	32.8	10	3 x 400-415V AC	10	2920	2.3	2" (50)	494	23499052
32796	32.8	10	3 x 400-415V AC	10	2920	2.3	2" (50)	494	23499051
38880	38.9	10	1 x 230V AC	10	2870	6.1	2" (50)	494	23499183
38880	38.9	10	1 x 230V AC	10	2870	6.1	2" (50)	494	23499181
38880	38.9	10	3 x 400-415V AC	10	2870	2.8	2" (50)	494	23499184
39240	39.2	10	1 x 230V AC	10	2870	6.1	2" (50)	494	23499182
39240	39.3	10	3 x 400-415V AC	10	2870	2.8	2" (50)	494	23499186
39240	39.2	10	3 x 400-415V AC	10	2870	2.8	2" (50)	494	23499185
44280	44.3	10	3 x 400-415V AC	10	2830	3.1	2" (50)	494	23499054
44280	44.3	10	3 x 400-415V AC	10	2830	3.1	2" (50)	494	23499055
44280	44.3	10	3 x 400-415V AC	10	2830	3.1	2" (50)	494	23499053
46440	46.4	10	3 x 400-415V AC	10	2720	3.8	2" (50)	494	23499028
46440	46.4	10	3 x 400-415V AC	10	2720	3.8	2" (50)	494	23499027
46440	46.4	10	3 x 400-415V AC	10	2720	3.7	2" (50)	494	23499026
									23499048

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.