



CPC Plug In-line Ferruleless Polytube Fitting PTF Series PMC

Characteristics

Series: PMC

Material: Acetal

Temperature range: -40 / 82 °C

Maximum operating pressure [Bar]: 8.3 bar

Description	Article
insert PMC2004 - PTF1/4 white acetal/Buna-N/non-valved	23277927
insert PMCD20M42 - PTF4mm white acetal/Buna-N/valved	23277978
insert PMC2006 - PTF3/8 white acetal/Buna-N/non-valved	11957458
insert PMCD2004 - PTF1/4 white acetal/Buna-N/valved	23277928
insert PMC20M42BLU - PTF4mm blue acetal/Buna-N/non-valved	23277996
insert PMC20M42 - PTF4mm white acetal/Buna-N/non-valved	23277977
insert PMCD2006 - PTF3/8 white acetal/Buna-N/valved	11957498
insert PMCD20025 - PTF5/32 white acetal/Buna-N/valved	23277926
insert PMC20025 - PTF5/32 white acetal/Buna-N/non-valved	23277925

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.