



GF Pipe Series: 480 PVDF

Characteristics

Series: 480

Material: PVDF

Pressure rating product: PN10/16

Length: 5 m

Diffusion-tight: No

Minimum medium temperature (continuous): 10 °C

Maximum medium temperature (continuous): 140 °C

Pipe colour: White

Outer pipe diameter mm	Wall thickness mm	Pressure rating	Article
16	1.9	PN16	11223675
20	1.9	PN16	11158350
25	1.9	PN16	11242792
32	2.4	PN16	11242873
50	3	PN16	11242874
63	3	PN16	11242877
75	3.6	PN16	11242878
90	3	PN10	11242917
90	4.3	PN16	11242879
110	3.4	PN10	11242918
110	5.3	PN16	11242880
125	3.9	PN10	11242919
125	6	PN16	11242881
140	4.4	PN10	11242923
140	6.7	PN16	11242882
160	4.9	PN10	11242920
160	7.7	PN16	11242913
200	6.2	PN10	11242921
200	9.6	PN16	11242914
225	7	PN10	11242922
225	10.8	PN16	11242915

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.