



GF Butterfly valve Series: 567 PP/PP Double-eccHandle Wafer type

Characteristics

Series: 567

Norm: EN (DIN)

Valve design: Double-eccentric

Housing material: PP

Connection: Wafer type

Face to Face norm: Manufacturer standard

Operation: Handle

Disk material: PP

Primary spindle seal material: FPM (FKM)

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length	Material liner	Spindle material	Quality class spindle	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Article
			mm				°C	°C	
DN50	PN10	PN10	45	EPDM	Stainless steel	1.4000	0	80	11378049
DN50	PN10	PN10	45	FPM (FKM)	Stainless steel	1.4000	0	80	11383609
DN65	PN10	PN10	46	EPDM	Stainless steel	1.4000	0	80	11383602
DN65	PN10	PN10	46	FPM (FKM)	Stainless steel	1.4000	0	80	11383611
DN80	PN10	PN10	49	EPDM	Stainless steel	1.4000	0	80	11378050
DN80	PN10	PN10	49	FPM (FKM)	Stainless steel	1.4000	0	80	11383612
DN100	PN10	PN10	56	EPDM	Stainless steel	1.4000	0	80	11383603
DN100	PN10	PN10	56	FPM (FKM)	Stainless steel	1.4000	0	80	11383613
DN125	PN10	PN10	64	EPDM	Stainless steel	1.4000	0	80	11383604
DN125	PN10	PN10	64	FPM (FKM)	Stainless steel	1.4000	0	80	11383615
DN150	PN10	PN10	72	EPDM	Stainless steel	1.4000	0	80	11383606
DN150	PN10	PN10	72	FPM (FKM)	Stainless steel	1.4000	0	80	11376717
DN200	PN10	PN10	73	EPDM	Stainless steel	1.4000	0	80	11383608
DN200	PN10	PN10	73	FPM (FKM)	Stainless steel	1.4000	0	80	11383618

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.