



SPIRAX SARCO Thermostatic valve fig. 9233 series KA33 cast iron flange

Characteristics

Series: KA33

Type: 9233

Housing material: Cast iron


Material quality: EN-JL1040

Pressure rating: PN16

Material disc: 1.4057

Spring material: Stainless steel

Maximum medium temperature (continuous): 220 °C



DN ["]	Max. diff. pressure [bar]	Kv- value	A mm	H mm	L mm	Weight [kg]
15	13	2,9	95	105	130	3,3
20	10,3	4,64	105	105	150	4,3
25	10,3	9,8	115	138	160	5,9
32	9	16,48	140	152	180	9,1
40	8,2	23,7	150	152	200	11,2
50	6,9	34	165	152	230	13,4

Design pressure	PN 16
Maximum temperature	220 °C

Connection	Nominal inner diameter	Maximum pressure difference bar	Kvs value	Article
Flange	DN15	13	2.9	11814943
Flange	DN20	10.3	4.64	11814944

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.