



FIP Branching Saddle Series: UFM PP-H Clamp feature Internal thread (BSPP)

Characteristics

Series: UFM
Shape: Broaching saddle
Material: PP-H
Connection: Internal thread (BSPP)
Suited for electrofusion fitting: No
Colour: Black
Clamp feature: Yes
Mounted on pipe: Clamp
Inlay material: NBR

Characteristics (2)

Minimum medium temperature (continuous): 0 °C
Maximum medium temperature (continuous): 100 °C
With cutter: No
Undrilled: No

Nominal inner diameter	External tube diameter of connection 2	Pressure rating	Number of scales	Width	Article
	mm			mm	
1/2"	40	PN10	2	51	10048528
1"	63	PN10	2	71	10048533
1.1/4"	90	PN10	2	91	11206410
1.1/4"	75	PN10	2	91	10048538
1.1/4"	110	PN10	2	98.5	10048546
1.1/4"	50	PN10	2	53	10048532
1.1/4"	160	PN10	2	137	10048552
1.1/2"	140	PN10	2	134	11965372
2"	90	PN10	2	91	10048539
2"	125	PN10	2	101	10048547

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.