



## FIP Branching Saddle Series: UFM PP-H Clamp feature Internal thread (BSPP)

### Characteristics

**Series:** UFM  
**Shape:** Broaching saddle  
**Material:** PP-H  
**Connection:** Internal thread (BSPP)  
**Suited for electrofusion fitting:** No  
**Colour:** Black  
**Clamp feature:** Yes  
**Mounted on pipe:** Clamp  
**Inlay material:** NBR

### Characteristics (2)

**Minimum medium temperature (continuous):** 0 °C  
**Maximum medium temperature (continuous):** 100 °C  
**With cutter:** No  
**Undrilled:** No

| Nominal inner diameter | External tube diameter<br>of connection 2 | Pressure rating | Number of scales | Width | Article  |
|------------------------|---|-----------------|------------------|-------|----------|
|                        | mm  |                 |                  | mm    |          |
| 1/2"                   | 40  | PN10            | 2                | 51    | 10048528 |
| 1"                     | 63  | PN10            | 2                | 71    | 10048533 |
| 1.1/4"                 | 90  | PN10            | 2                | 91    | 11206410 |
| 1.1/4"                 | 75  | PN10            | 2                | 91    | 10048538 |
| 1.1/4"                 | 110                                       | PN10            | 2                | 98.5  | 10048546 |
| 1.1/4"                 | 50  | PN10            | 2                | 53    | 10048532 |
| 1.1/4"                 | 160                                       | PN10            | 2                | 137   | 10048552 |
| 1.1/2"                 | 140                                       | PN10            | 2                | 134   | 11965372 |
| 2"                     | 90  | PN10            | 2                | 91    | 10048539 |
| 2"                     | 125                                       | PN10            | 2                | 101   | 10048547 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.