



FIP Branching Saddle Series: UIFV PVC-U Clamp feature Internal thread (BSPP)

Characteristics

Series: UIFV
Shape: Broaching saddle
Material: PVC-U
Connection: Internal thread (BSPP)
Suited for electrofusion fitting: No
Colour: Grey
Clamp feature: Yes
Mounted on pipe: Clamp
Inlay material: NBR

Characteristics (2)

Minimum medium temperature (continuous): 0 °C
Maximum medium temperature (continuous): 60 °C
With cutter: No
Undrilled: No

Nominal inner diameter	External tube diameter of connection 2	Pressure rating	Number of scales	Width	Article
	mm			mm	
3/4"	40	PN16	2	51	11323136
3/4"	110	PN16	2	105	10048569
1"	40	PN16	2	51	10048555
1"	140	PN16	2	114	10048574
1.1/2"	75	PN16	2	105	10048564
1.1/2"	140	PN16	2	114	10048576
1.1/2"	160	PN16	2	120	10048580
1.1/2"	225	PN16	2	125	10048583
2"	200	PN16	2	133	10048581
2"	225	PN16	2	125	10048582

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.