



Hose EF-1 NEO, ventilation hose for hot air up to 150 °C, 1-ply neoprene glass fibre coated with exposed steel helix

Application

suction and blower hose for cold and hot air, smoke, gases, etc.

Temperature range

-35 °C to +150 °C continuous

Properties

exposed steel spiral with fiberglass cloth, neoprene impregnated fiberglass cord

Connections

free of choice or to be mounted directly on pipe

Assembly

FIXXED hose clamps

Internal diameter	Outer diameter	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	bar	%	mm	m	
25	52	1.6	51	32	4	10015585
32	70.8	1.4	48	48	4	11074790
38	78.2	1.4	46	52	4	10015586
44	84.4	1.25	44	64	4	10015587
51	88.6	1.2	43	67	4	10015588
57	99.2	1.15	38	67	4	10015589
63	42.2	1.15	37	89	4	10015590
70	49.6	1.12	35	93	4	10015591
76	23	1.1	34	101	4	10015592
83	27	1.05	30	115	4	10015593
90	15.8	1	28	125	4	10015594
95	19.4	0.95	27	130	4	10015595
102	109.4	0.9	26	136	4	10015596
110	119.8	0.87	23	150	4	10015597
114	130	0.85	20	155	4	10015598
120	135.2	0.82	19	160	4	10015599
127	161.8	0.8	17	178	4	10015600
130	23.8	0.8	15	181	4	11380866
140	30	0.7	14	194	4	10015601
152	35.4	0.7	14	205	4	10015602
160	37.4	0.7	14	205	4	11077410
180	40.6	0.6	10	240	4	10015603
203	46.4	0.55	7	290	4	10015604
254	62.4	0.5	5	354	4	10015605
305	67.6	0.35	5	435	4	10015606
						11687647

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.