

# E-COLL Drilling oil concentrate type 9826

#### **Product description**

- White, completely stable and homogenous emulsion.
- Immune to hardness ranges in water (lime, etc.).
- Largely resistant to microbial attack, physiologically safe (with correct use).

## **Application**

#### **Application areas**

- Emulsifier for drills, turners, mills, saws and thread
- For aluminium, non-ferrous metals and their alloys, cast- and stainless steel.

#### **Technical Information**

#### **Technical characteristics**

• Contains mineral oil EP-drilling compound, chlorine-

### **Application concentration:**

• Milling: ca. 8% strength [11 concentration in 11 litres of water). Sawing, turning, drilling: ca. 10% (11 concentrate in 10 I water). Thread cutting: ca. 10% (1 I concentrate in 10 I water).Long tool life.

Packaging	Volume	Article
	1	
Bottle	1	23429946
Jerrycan	5	23429944
Jerrycan	10	23429945

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR\_EC011130\_0006\_MVB\_EN\_28.09.2024