




ECON® Bourdon tube pressure gauge Type 1414 bottom connection brass

Characteristics

Type: 1414
Model: Bourdon tube pressure gauge
Blow-out included: No
Pressure gauge attachment: Direct
Process connection: External thread
Cabinet material: Stainless steel 304
Process connection material: Brass

Characteristics [2]

Window material: Acrylic
Material dial: Aluminium
Protection class: IP65
Medium temperature: -20 / 50 °C
Ambient temperature: -20 / 50 °C



Cabinet diameter	G	D	b	a	c	c1	c2	h	s1	SW	Gewicht
mm	BSPP	mm	mm	mm	mm	mm	mm	mm	mm	mm	Kg
R63	1/4"	67	32	10	5	2	13	54	6.5	17	0.25
R100	1/2"	100	37	10	6	3	17	81	10	22	0.6

Cabinet diameter	Measuring range	Pressure unit	Secondary scale division	Pressure unit secondary scale	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Maximum overpressure	Article
mm									bar	
63	-1 / 1.5	bar			1.6 %	Glycerin	Below	1/4" BSPP[G]	1.9	11037757
63	0 / 60	bar			1.6 %	Glycerin	Below	1/4" BSPP[G]	78	11037795
63	0 / 60	bar	0 - 800	psi	1.6 %	Glycerin	Below	1/4" BSPP[G]	78	10060889
63	0 / 160	bar			1.6 %	Glycerin	Below	1/4" BSPP[G]	208	11037797
63	0 / 160	bar	0 - 2000	psi	1.6 %	Glycerin	Below	1/4" BSPP[G]	208	10060902
63	0 / 250	bar			1.6 %	Glycerin	Below	1/4" BSPP[G]	325	10059747
63	0 / 400	bar			1.6 %	Glycerin	Below	1/4" BSPP[G]	520	11037799
63	0 / 400	bar	0 - 6000	psi	1.6 %	Glycerin	Below	1/4" BSPP[G]	520	10060900
63	0 / 600	bar			1.6 %	Glycerin	Below	1/4" BSPP[G]	780	11129477
100	-1 / 0	bar			1.6 %	Glycerin	Below	1/2" BSPP[G]	0	12308627

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.