



ECON® Bourdon tube pressure gauge Type: 3660 bottom connection brass

Characteristics

Type: 3660
Model: Bourdon tube pressure gauge
Blow-out included: No
Pressure gauge attachment: Direct
Process connection: External thread
Process connection material: Brass
Window material: Plastic
Material dial: Aluminium
Protection class: IP65
Medium temperature: -20 / 60 °C
Ambient temperature: -20 / 60 °C

Application


- Industry.
- Installation technology.
- Hydraulics.

Technical Information

- Suitable for gases and liquids that do not affect the brass measuring system.
- Suitable for outdoor installation.
- Glycerine filling for damping of mechanical vibrations.
- Measuring ranges according to EN 837-1.

Options

- Damping screw in the connection.
- Process connection NPT.



Size table:

Cabinet diameter	G	a	b	D1	D2	e	h	SW	Weight
		mm	mm	mm	mm	mm	mm	mm	kg
R63	1/4"	13	32	68	62	6.5	54	14	0.21
R80	1/2"	9.5	32	83.5	80	5.5	71	22	0.7
R100	1/2"	15.5	48	107	100	8	87	22	0.8

Cabinet diameter	Measuring range	Pressure unit	Pressure unit secondary scale	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Cabinet material	Maximum overpressure	Article
mm									bar	
63	-1 / 0	bar		1.6 %	Glycerin	Below	1/4" BSPP[G]	Stainless steel 304	0	12035813
63	-1 / 0.6	bar		1.6 %	Glycerin	Below	1/4" BSPP[G]	Stainless steel 304	0.6	12035814
63	-1 / 1.5	bar		1.6 %	Glycerin	Below	1/4" BSPP[G]	Stainless steel 304	1.5	12035815
63	-1 / 3	bar		1.6 %	Glycerin	Below	1/4" BSPP[G]	Stainless steel 304	250	12035816
63	-1 / 5	bar		1.6 %	Glycerin	Below	1/4" BSPP[G]	Stainless steel 304	5	12035817
63	-1 / 9	bar		1.6 %	Glycerin	Below	1/4" BSPP[G]	Stainless steel 304	9	12035818

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Cabinet diameter	Measuring range	Pressure unit	Pressure unit secondary scale	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Cabinet material	Maximum overpressure	Article
mm									bar	
63	0 / 0.6	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	0.6	12693877
63	0 / 1	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	1	12035835
63	0 / 1.6	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	1.6	12035820
63	0 / 2.5	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	2.5	12035822
63	0 / 4	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	4	12035823
63	0 / 6	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	6	12035824
63	0 / 10	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	10	12035825
63	0 / 16	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	16	12035826
63	0 / 16	bar	psi	1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	16	14528682
63	0 / 25	bar	psi	1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	25	14528683
63	0 / 25	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	25	12035827
63	0 / 40	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	40	12035828
63	0 / 60	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	600	12035829
63	0 / 60	bar	psi	1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	60	14528677
63	0 / 100	bar	psi	1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	100	14528678
63	0 / 100	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	100	12035830
63	0 / 160	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	160	12035831
63	0 / 160	bar	psi	1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	160	14528681
63	0 / 250	bar	psi	1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	250	14528680
63	0 / 250	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	250	12035832
63	0 / 400	bar	psi	1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	400	14528679
63	0 / 400	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	400	12035833
63	0 / 600	bar		1.6 %	Glycerin	Below	1/4" BSPP(G)	Stainless steel 304	600	12035834
80	-1 / 0.6	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	0.6	12725609
80	-1 / 9	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	9	12584679
80	0 / 1.6	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	1.6	12725601
80	0 / 2.5	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	2.5	12725604
80	0 / 10	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	10	12725602
80	0 / 25	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	25	12725605
80	0 / 40	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	40	12725606
100	-1 / 0	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	0	12035836
100	-1 / 0.6	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	0.8	12035837
100	-1 / 0.6	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	0.8	13367496
100	-1 / 1.5	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	1.9	12035838

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Cabinet diameter	Measuring range	Pressure unit	Pressure unit secondary scale	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Cabinet material	Maximum overpressure	Article
mm									bar	
100	-1 / 1.5	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	1.9	13367488
100	-1 / 3	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	3.9	13367490
100	-1 / 3	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	3.9	12035839
100	-1 / 5	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	6	12035840
100	-1 / 5	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	6	13367493
100	-1 / 9	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	11	12035841
100	-1 / 15	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	19	13367494
100	-1 / 15	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	19	12035842
100	0 / 1	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	1.3	13367482
100	0 / 1	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	1.3	12035844
100	0 / 1.6	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	2	13367480
100	0 / 2.5	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	3	13305844
100	0 / 2.5	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	3	12035846
100	0 / 4	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	5	13367477
100	0 / 4	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	5	12035847
100	0 / 6	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	7.8	13367475
100	0 / 6	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	7.8	12035848
100	0 / 10	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	13	12035849
100	0 / 10	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	13	12979700
100	0 / 16	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	20	13308325
100	0 / 16	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	20	12035850
100	0 / 25	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	32	12035851
100	0 / 25	bar		1.6 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	32	13367484
100	0 / 40	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	52	12035852
100	0 / 60	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	78	12035853
100	0 / 100	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	130	12035854
100	0 / 160	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	208	12035855
100	0 / 250	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	325	12035856
100	0 / 400	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	520	12035857
100	0 / 600	bar		1.0 %	Glycerin	Below	1/2" BSPP(G)	Stainless steel 304	780	12035858

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.