




## ECON® Float switch fig. 8400 plastic horizontal external thread

### Characteristics

**Type:** 8400  
**Process connection:** External thread [BSPP]  
**Contact type:** 1 x NO of 1 x NC  
**Contact version:** Silver  
**Switching power:** 230V AC / 1A / 26VA - 48V DC / 1A / 20W  
**Adjustable differential gap:** No  
**Switching differential:** 1 - 4 mm

### Characteristics [2]

**Housing material:** Plastic  
**Float material:** PVDF  
**Material cover:** Plastic  
**With sleeve:** No  
**Level of protection (IP value):** IP65  
**Ambient temperature:** -25 / 80 °C



G [BSPP]	A [mm]	B [mm]	C [mm]	D [mm]
3/4"	22	49	141	93

Model	Mounting	Size process connection	Max. operating pressure bar	Min. specific density of liquid kg/m <sup>3</sup>	Float diameter mm	Material wet portion housing	Material insert	Material of connection	Medium temperature °C	Article
Horizontal float switch	Horizontal	3/4" [20]	25	780	22	Brass	Brass	Brass	-10 / 110	11814885
Horizontal float switch	Horizontal	3/4" [20]	10	780	22	Plastic	Plastic	Stainless steel	-10 / 100	11814884
Horizontal float switch	Horizontal	3/4" [20]	25	780	22	Stainless steel	Stainless steel	Stainless steel	-10 / 110	11814886

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.