

MOBREY Float switch fig. 8340 aluminium horizontal flange



Characteristics

Series: S417DA

Type: 8340

Process connection: Flange


Contact version: Silver

Switching power: 440V / 5A / 2000VA AC - 240V / 1A
/ 35W DC inductive - 240V / 1A / 35W DC resistive

Adjustable differential gap: No

Switching differential: 13 mm

Housing material: Aluminium alloy



uitvoering met FB4 vlotter

Characteristics [2]

Material wet portion housing: Stainless steel 316

Float material: Stainless steel 316

Material cover: Aluminium alloy

Material of connection: Steel

With sleeve: No

Ambient temperature: -30 / 70 °C

Explosion-proof: No

Model	Mounting	Size process connection	Standard connection	Pressure rating flange	Max. operating pressure bar	Min. specific density of liquid kg/m ³	Float diameter mm	Contact type	Level of protection (IP value)	Article
Horizontal float switch	Horizontal	3" [80]	ASME	Class 300	34.5	600	65	1 x NO en 1 x NC	IP66	12036207
Horizontal float switch	Horizontal	DN65	(EN) DIN	PN16	16	650	65	1 x NO en 1 x NC	IP66	12036208
Horizontal float switch	Horizontal	DN65	(EN) DIN	PN40	40	600	65	1 x NO en 1 x NC	IP65	12036205
Horizontal float switch	Horizontal	DN65	(EN) DIN	PN40	40	650	65	1 x NO en 1 x NC	IP66	12036204
Horizontal float switch	Horizontal	DN80	(EN) DIN	PN40	40	510	65	1 x NO en 1 x NC	IP66	12036206
Horizontal float switch	Horizontal	DN80	(EN) DIN	PN16	16	650	65	1 x NO en 1 x NC	IP66	12036209

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.