

Safety clamp coupling in stainless steel with male thread type ECM



Characteristics

Type of component: Hose tail coupling

Material: Stainless steel (AISI 316)

Connection type: Threaded coupling

Hose fitting type: Male thread

Connection termination: NPT

Elbow angle [degr.]: 0 °

Hose tail execution: Smooth, with safety collar

Temperature range [°C]: -40 / 150 °C



Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
				13562357
1/2"	DN12	25	362	10039036
1"	DN19	25	362	10039050
3/4"	DN19	25	362	10039042
1"	DN25	25	362	10039049
2"	DN25	25	362	10070344
2"	DN32	25	362	10070351
1.1/2"	DN32	25	362	10070349
1.1/2"	DN38	25	362	10039059
2"	DN38	25	362	10070357
2.1/2"	DN50	25	362	10070449
2"	DN50	25	362	10039066
3"	DN63	25	362	10070365
2.1/2"	DN63	25	362	10070364
3"	DN75	25	362	10039072
4"	DN100	25	362	10039030
1/2"	DN12	25	362	11114206
3/4"	DN19	25	362	10039043
1"	DN25	25	362	10039051
1.1/4"	DN32	25	362	10070347
1.1/2"	DN38	25	362	10070356
2"	DN50	25	362	10070363
3"	DN75	25	362	10070372
4"	DN100	25	362	10070378

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.