



## Flange coupling type SHFF-HP, fixed flange EN 1092-1 according to EN14423

### Characteristics

**Type:** SHFF-HP

**Type of component:** Hose tail coupling

**Material:** Steel

**Connection type:** Flange

**Hose fitting type:** Fixed flange

**Connection termination:** EN1092 PN40

**Seal material:** Novatec

**Elbow angle [degr.]:** 0 °

**Hose tail execution:** Smooth, with safety collar

**Temperature range [°C]:** -40 / 232 °C

Connection termination size	Hose ID [DN]	Maximum operating pressure		Article
		bar	psi	
DN40	DN40	18	261	13580447
DN50	DN50	18	261	13580437
3/4"	DN19	18	261	13530629
3/4"	DN19	18	261	11343068
1.1/2"	DN38	18	261	13530632
DN 15	DN12	18	261	10037928
2"	DN50	18	261	13530633
DN50	DN50	18	261	13580498
DN32	DN32	18	261	13530631

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.