



Bauer coupling casted steel (f)/hose pillar S78

Characteristics

Type of component: Hose tail coupling

Material: Steel

Connection type: Quick Coupling

Hose fitting type: Bauer

Connection termination: Female

Seal material: NBR

Elbow angle [degr.]: 0 °

Hose tail execution: Rolled

Temperature range [°C]: -40 / 80 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
108 mm		5	73	12618367
50 mm	DN38	5	72	12618360
108 mm	DN50	5	72	12618364
50 mm	DN50	5	72	11012863
76 mm	DN63	5	72	12618361
76 mm	DN75	5	72	12618362
89 mm	DN75	5	72	11036079
108 mm	DN75	5	72	12618365
108 mm	DN90	5	72	12618366
89 mm	DN90	5	72	12618363
133 mm	DN100	5	72	12618368
108 mm	DN100	5	72	10037590
133 mm	DN125	5	72	12618369
159 mm	DN125	5	72	12618370
159 mm	DN150	5	72	11016692
194 mm	DN200	5	72	11083136

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.