



## ERIKS Rubber sheet CR/SBR 65 NEOPRENE 642RV 131203

### Characteristics

**Series:** CR/SBR 65

**Type:** NEOPRENE 642RV

**Max. pressure:** 5 bar

**Colour:** Black

**Temperature range:** -30 / 70 °C

**Suitable for medium:** Air [compressed air], Water [process water], Weak Acids, Water, Weak Alkalis, Alkalis

Thickness mm	Length mm	Width mm	Number of inserts	Article
0.5	10000	1200		11195529
1	20000	1400		10017169
1.5	15000	1400		10017170
2	20000	1400		10017171
2	20000	1400	1	10017180
3	10000	1400		10017172
3	10000	1400	1	10017181
4	10000	1400	1	11146765
4	10000	1400		10017173
5	10000	1400	1	10017182
5	10000	1400		10017174
6	10000	1400		10017175
8	5000	1400		10017176
10	5000	1400		10017177
15	5000	1400		10017178
20	5000	1400		10017179

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.