

## GATES Hydraulic hose M4K-XTF (R19) XtraTuff™



### Characteristics

- Type:** M4K-XTF
- Material of inner wall:** NBR
- Material of outer wall:** NBR/PVC
- Quality cover:** Gates XtraTuff
- Temperature range [°C]:** -40 / 100 °C
- EN standard:** EN 857-2SC
- SAE standard:** SAE 100 R19
- ISO standard:** ISO 11237 R19

### Application

- Recommended for high-pressure hydraulic applications.
- Easy to route and to install in tight areas.

### Technical Information

- Temperature range:**
- -40°C to +100°C constant and +121°C intermittent.

### Construction

- Tube:**
- NBR (Nitrile) based.
- Reinforcement:**
- Two braids of high tensile steel wire.
- Cover:**
- NBR/PVC based.
- MSHA approved.
- XtraTuff™.

### Execution

- 50% of EN 857 2SC and 40% of EN 853 2SN bend radius at rated working pressure.
- Alternative to spiral hoses in high pressure lines where flexibility is required.
- Superior flex impulse performance: tested to 600,000 impulse cycles.
- M4K-XTF hose is compatible with biodegradable hydraulic fluids like synthetic esters, polyglycols and vegetable oils as well as petroleum-based fluids.
- Gates special XtraTuff™ cover offers 25 times the abrasion resistance of the standard M4K cover as per ISO 6945.0

### Approval

#### Standards:

- Exceeds ISO 11237 R19. SAE 100 R19.
- Meets or exceeds EN 857 2SC performance requirements.

#### Type approval:

- DNV

### Options

#### Recommended couplings:

- MegaCrimp®

Code	Hose ID (DN)	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Weight	Article
		in	mm	bar	bar	mm			
4M4K-XTFXRL134	DN06	1/4"	14	280	1120	40	Black	0.33	1033063
5M4K-XTFXRL107	DN08	5/16"	15.5	280	1120	45	Black		14606988
6M4K-XTFXRL101	DN10	3/8"	17.8	280	1120	50	Black	0.46	1033065
8M4K-XTFXRL67	DN12	1/2"	21.3	280	1120	70	Black	0.51	1033064
10M4K-XTFXRL67	DN16	5/8"	25.1	280	1120	75	Black	0.74	11374400
12M4K-XTFXRL67	DN19	3/4"	29.7	280	1120	95	Black	0.93	11374401

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.