

GATES Hydraulic hose EFG6K (R15)

Characteristics

Type: EFG6K
Material of inner wall: NBR
Material of outer wall: CR
Quality cover: Standard
Temperature range [°C]: -40 / 121 °C
SAE standard: SAE 100 R15
ISO standard: ISO 3862 R15

Application

- Extremely high pressure and high impulse hydraulic applications.

Technical Information

Temperature range:

- 40°C to +121°C

Construction

Tube:

- NBR (Nitrile) based.

Reinforcement:

- Four (six for -20 to -32) alternating layers of spiralled, high tensile steel wire.

Cover:

- CR (Chloroprene) based.
- MSHA approved.

Execution

- Up to 40% of EN 856 4SP/4SH bend radius at rated working pressure.
- Extremely flexible.
- Superior flex impulse performance: tested to 1,000,000 impulse cycles at 50% of SAE 100R15 bend radii [except -32].
- EFG6K hose is compatible with biodegradable hydraulic fluids like synthetic esters, polyglycols and vegetable oils as well as petroleum-based fluids.

Approval

Standards:

- Exceeds ISO 3862 R15. SAE 100 R15.
- Meets or exceeds performance requirements of EN 856 4SP [-10 to -32] and EN 856 4SH [-20 to -32].

Type approval:

- DNV, LR, BV and ABS.

Options

Recommended couplings:

- 6 to -20: GlobalSpiral
- 24, -32: GlobalSpiral Maximum



Code	Hose ID [DN]	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Weight	Article
		in							
6EFG6K	DN10	3/8"	20.3	420	1680	65	Black	0.71	791024
8EFG6KXLL	DN12	1/2"	24.1	420	1680	90	Black	0.89	791164
10EFG6KXLL	DN16	5/8"	27.7	420	1680	100	Black	1.15	795771
12EFG6KXLL	DN19	3/4"	31.5	420	1680	120	Black	1.44	795887
16EFG6KXBALE	DN25	1"	38.9	420	1680	150	Black	2.23	795909
20EFG6KXLL	DN31	1.1/4"	50	420	1680	210	Black	3.99	796050
24EFG6KXLL	DN38	1.1/2"	57.4	420	1680	250	Black	4.82	11276963
32EFG6K	DN51	2"	71.1	420	1680	635	Black	7.19	12448183

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.