

GATES Hydraulic hose EFG6K-MTF (R15) MegaTuff™

Characteristics

Type: EFG6K-MTF
Material of inner wall: NBR
Material of outer wall: CR
Quality cover: Gates Megatuff
Temperature range [°C]: -40 / 121 °C
SAE standard: SAE 100 R15
ISO standard: ISO 3862 R15

Application

- Extremely high pressure and high impulse hydraulic applications.

Technical Information

Temperature range:

- -40°C to +121°C

Construction

Tube:

- NBR (Nitrile) based.

Reinforcement:

- Four (six for -20 to -32) alternating layers of spiralled, high tensile steel wire.

Cover:

- CR (Chloroprene) based.
- MSHA approved.
- MegaTuff™

Execution

- Up to 40% of EN 856 4SP/4SH bend radius at rated working pressure.
- Extremely flexible.
- Superior flex impulse performance: tested to 1,000,000 impulse cycles at 50% of SAE 100R15 bend radii [except -32].
- EFG6K-MTF hose is compatible with biodegradable hydraulic fluids like synthetic esters, polyglycols and vegetable oils as well as petroleum-based fluids.
- Gates special MegaTuff™ cover offers 300 times the abrasion resistance of the standard EFG6K cover as per ISO 6945, superior ozone and weathering resistance.

Approval

Standards:

- Exceeds ISO 3862 R15. SAE 100 R15.
- Meets or exceeds performance requirements of EN 856 4SP [-8 to -32] and EN 856 4SH [-12 to -32].

Type approval:

- DNV

Options

Recommended couplings:

- -6 to -20: GlobalSpiral
- -24, -32: GlobalSpiral Maximum



Code	Hose ID (DN)	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Weight	Article
		in							
6EFG6K-MTF	DN10	3/8"	20.3	420	1680	65	Black	0.71	949043
8EFG6K-MTF	DN12	1/2"	24.1	420	1680	90	Black	0.89	949051
10EFG6K-MTF	DN16	5/8"	27.7	420	1680	100	Black	1.15	949086
12EFG6K-MTF	DN19	3/4"	31.5	420	1680	120	Black	1.44	1028095
16EFG6K-MTF	DN25	1"	38.9	420	1680	150	Black	2.23	1021941
20EFG6K-MTF	DN31	1.1/4"	50	420	1680	210	Black	3.99	11320354
24EFG6K-MTF	DN38	1.1/2"	57.4	420	1680	250	Black	4.82	12448184
32EFG6K-MTF	DN51	2"	71.1	420	1680	635	Black	7.19	12448185

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.