

GATES Low pressure rubber hose GTH

Characteristics

Series: MegaSys®

Type: GTH

Material of inner wall: NBR

Material of outer wall: CR

Quality cover: Standard

Temperature range [°C]: -40 / 135 °C

EN standard: EN 854-R6

SAE standard: SAE 100 R6

ISO standard: ISO 4079 R6

Application

- Recommended for high-temperature, low pressure hydraulic oil lines, heavy-duty transmission oil cooler lines and glycol anti-freeze solutions.

Technical Information

Temperature range:

- -40°C to +135°C constant and +150°C intermittent.

Construction

Tube:

- NBR (Nitrile) based.

Reinforcement:

- One fibre braid.

Cover:

- CR (Chloroprene) based.

Approval

Standards:

- :Meets ISO 4079 R6 / EN 854 R6 / SAE 100 R6 [-4 to -12].

Options

Recommended couplings:

- MegaCrimp®



Code	Hose ID (DN)	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Weight	Article
		in	mm	bar	bar	mm		kg/m	
4GTH	DN06	1/4"	12.7	280	112	65	Black	0.13	1028767
5GTH	DN08	5/16"	14.3	280	112	75	Black	0.15	11374443
8GTH	DN12	1/2"	19.8	280	112	100	Black	0.23	1008584
10GTH	DN16	5/8"	23	240	96	125	Black	0.28	940461

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.