



Rubber paint spray hose Oliva PA, electrically conductive Ω



Application

- flexible, kink free paint hose
- suitable for transport of polar and aromatic solvents, paints, lacquers, glue and oils

Technical Information

Temperature range

- -25 °C to +80 °C continuous

Burst pressure

- minimum 100 bar
- safety factor 4:1

Construction

Tube

- black PA
- smooth and wear resistant
- electrically conductive $R < 10^6 \Omega$

Reinforcement

- spiral-ply synthetic fabrics with high tensile strength

Cover

- grey NBR rubber
- ozone and weather resistant
- electrically conductive $R < 10^6 \Omega$

Execution

Branding

- black text: "CONTI - M-R < 1.000.000 OHM"

Connections

- free of choice

Assembly

- FIXXED hose clamps or ferrules

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum bending radius	Roll length	Article
mm	mm	mm	bar	mm	m	
8	3	14	25	80	20	12331001
9	3,5	16	25	90	20	12331013
11	4	19	25	110	20	12331016
13	3,5	20	25	130	20	12331017

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.