

# GOODALL Rubber hose Guardian, low pressure steam hose 6 bar



## Characteristics

**Series:** Guardian

## Application

- hot water and open steam hose for general industrial applications
- hot water up to 90 °C open steam up to 164 °C and 6 bar

## Technical Information

### Temperature range

- -40 °C to +164 °C

### Burst pressure

- burst pressure minimum 60 bar
- safety factor hot water 4:1
- safety factor steam 10:1

### Note

- all technical specifications apply to a temperature of 20°C
- refer to the Goodall resistance list or, in case of doubt, contact ERIKS

## Construction

### Tube

- black, conductive EPDM rubber

### Reinforcement

- spiral-plyed synthetic fabrics

### Cover

- black, conductive EPDM rubber
- cloth impression
- durable
- wear resistant
- ozone resistant

### Branding

- red marking with text: "GOODALL GUARDIAN - STEAM 6 BAR 164°C / 90 PSI 330°F Ω"

## Options

### Complete assembly

- ERIKS can assemble the Guardian with the required fittings, using different assembling techniques like ferrules, safety clamps, ...

### Options

- hydrostatic test report
- conductivity test
- excellent laser engraving on marking ferrule

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	mm	m	kg/m	
13	5	23	6	60	130	61	0.37	10015273
16	5	26	6	60	160	61	0.42	10015274
19	5	29	6	60	190	61	0.47	10015275
25	5	35	6	60	250	61	0.58	10015276
32	7	46	6	60	320	61	0.95	10015277

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.