

Rubber hose Performer GL AD10H, abrasion resistant NR suction & discharge hose 10 bar



Application

- abrasion resistant suction and discharge hose for transporting wearing media by air and/or water, such as plaster, ashes, bauxite, corundum, dolomite, ores, feldspar, waste glass, wood chips, industrial waste, coal, metallic powder, etc.

Technical Information

Temperature range

- -30 °C to +70 °C

Burst pressure

- minimum 30 bar
- safety factor 3:1

Construction

Tube

- black NR rubber
- smooth
- wear resistant

Reinforcement

- synthetic textile fabrics
- completely embedded steel spiral, vacuum resistant

Cover

- black EPDM rubber, corrugated
- cloth impression
- weather resistant

Execution

Branding

- green/red marking with text: "PERFORMER GL AD10H"

Assembly

- special full-bore flange coupling system without hose shank, type BLOC-END®

Internal diameter mm	Wall thickness mm	Roll length m	Weight kg/m	Article
80	8.5	20	5.9	23279236

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.