

MECAFRANCE Ball valve Type: 3463 Steel Internal thread (BSPP) PN50 to PN100

Characteristics


Type: 3463 Norm: EN (DIN)

Construction type: 2-way Housing construction: 3-part Housing material: Steel Material quality: 1.0619

Connection: Internal thread (BSPP) Top flange standard: ISO 5211 Tertiary spindle seal material: RPTFE

Body seal: PTFE

Actuator material: Steel



Nominal inner diameter	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
1/2" (15)	PN100	Manufacturer standard	Handle	F03	Full bore	1.4408	PTFE	1.4404	RPTFE	12571017
3/4" (20)	PN100	Manufacturer standard	Handle	F04	Full bore	1.4408	PTFE	1.4404	RPTFE	12571018
1" (25)	PN80	Manufacturer standard	Handle	F04	Full bore	1.4408	PTFE	1.4404	RPTFE	12571019
1.1/4" (32)	PN63	Manufacturer standard	Handle	F05	Full bore	1.4408	PTFE	1.4404	RPTFE	12571020
1.1/2" [40]	PN63	Manufacturer standard	Handle	F05	Full bore	1.4408	PTFE	1.4404	RPTFE	12571021
2" (50)	PN50	Manufacturer standard	Handle	F07	Full bore	1.4408	PTFE	1.4404	RPTFE	12571022

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1