



GF Ball valve Series: 546 PP-H Silicone-free Plastic welded sleeve PN10

Characteristics

Series: 546

Construction type: 2-way

Housing construction: 3-part

Housing material: PP-H

Connection: Plastic welded sleeve

Silicone-free: Yes

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Material ball	Seat material	Primary spindle seal material	Secondary spindle seal material	Body seal	Article
DN15	20	PN10	Manufacturer standard	Handle	PP-H	PTFE	EPDM	EPDM	EPDM	11308650
DN20	25	PN10	Manufacturer standard	Handle	PP-H	PTFE	EPDM	EPDM	EPDM	11458346
DN25	32	PN10	Manufacturer standard	Handle	PP-H	PTFE	EPDM	EPDM	EPDM	11308630
DN32	40	PN10	Manufacturer standard	Handle	PP-H	PTFE	EPDM	EPDM	EPDM	12583396
DN40	50	PN10	Manufacturer standard	Handle	PP-H	PTFE	EPDM	EPDM	EPDM	11308629

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.