



## GF Ball valve Series: 546 PP-H Flange PN10

### Characteristics

**Series:** 546  
**Construction type:** 2-way  
**Housing construction:** 3-part  
**Housing material:** PP-H  
**Connection:** Flange  
**Pressure rating:** PN10  
**Manual operation:** Handle  
**Bore:** Full bore  
**With locking device:**  
**Material ball:** PP-H  
**Seat material:** PTFE

Nominal inner diameter	External tube diameter of connection	Face to Face norm	Spindle material	Primary spindle seal material	Secondary spindle seal material	Body seal	Minimum medium temperature (continuous) °C	Maximum medium temperature (continuous) °C	With drain	Article
mm										
DN15	20			EPDM	EPDM	EPDM				11291092
DN15	20	Manufacturer standard	PP	FPM (FKM)	FPM (FKM)	FPM (FKM)	10	95	No	11308627
DN20	25			EPDM	EPDM	EPDM				11291093
DN20	25	Manufacturer standard	PP	FPM (FKM)	FPM (FKM)	FPM (FKM)	10	95	No	11308626
DN25	32			EPDM	EPDM	EPDM				11291094
DN25	32	Manufacturer standard	PP	FPM (FKM)	FPM (FKM)	FPM (FKM)	10	95	No	11308625
DN32	40			EPDM	EPDM	EPDM				11291095
DN32	40	Manufacturer standard	PP	FPM (FKM)	FPM (FKM)	FPM (FKM)	10	95	No	11516292
DN40	50			EPDM	EPDM	EPDM				11291096
DN40	50	Manufacturer standard	PP	FPM (FKM)	FPM (FKM)	FPM (FKM)	10	95	No	11310262
DN50	63			EPDM	EPDM	EPDM				11286545
DN50	63	Manufacturer standard	PP	FPM (FKM)	FPM (FKM)	FPM (FKM)	10	95	No	11308624

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.