



GF Ball valve Series: 546 PP-H Flange PN10

Characteristics

Series: 546
Construction type: 2-way
Housing construction: 3-part
Housing material: PP-H
Connection: Flange
Primary spindle seal material: FPM (FKM)
Secondary spindle seal material: FPM (FKM)

Characteristics [2]

Body seal: FPM (FKM)
Minimum medium temperature (continuous): 10 °C
Maximum medium temperature (continuous): 95 °C
With drain: No

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Material ball	Seat material	Spindle material	Article
DN15	20	PN10	Manufacturer standard	Handle	Full bore		PP-H	PTFE	PP	11308627
DN20	25	PN10	Manufacturer standard	Handle	Full bore		PP-H	PTFE	PP	11308626
DN25	32	PN10	Manufacturer standard	Handle	Full bore		PP-H	PTFE	PP	11308625
DN32	40	PN10	Manufacturer standard	Handle	Full bore		PP-H	PTFE	PP	11516292
DN40	50	PN10	Manufacturer standard	Handle	Full bore		PP-H	PTFE	PP	11310262
DN50	63	PN10	Manufacturer standard	Handle	Full bore		PP-H	PTFE	PP	11308624

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.