



FIP Ball valve Series: VKDIM PP-H Plastic welded sleeve PN10

Characteristics

Series: VKDIM

Construction type: 2-way

Housing construction: 3-part

Housing material: PP-H

Connection: Plastic welded sleeve

Material ball: PP-H

Seat material: PTFE

Spindle material: PP-H

Minimum medium temperature (continuous): 10 °C

Maximum medium temperature (continuous): 95 °C

With drain: No

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Primary spindle seal material	Secondary spindle seal material	Body seal	Article
DN15	20	PN10	Manufacturer standard	Handle	Full bore		FPM (FKM)	FPM (FKM)	FPM (FKM)	10055199
DN20	25	PN10	Manufacturer standard	Handle	Full bore		EPDM	EPDM	EPDM	10055191
DN20	25	PN10	Manufacturer standard	Handle	Full bore		FPM (FKM)	FPM (FKM)	FPM (FKM)	10055200
DN25	32	PN10	Manufacturer standard	Handle	Full bore		EPDM	EPDM	EPDM	10055192

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.