

## BAC Ball valve Series: PQRI Type: 7371 Stainless steel Fire safe Flange Class 300



### Characteristics

**Series:** PQRI

**Type:** 7371

**Norm:** ASME

**Construction type:** 2-way

**Housing construction:** 1-part

**Housing material:** Stainless steel

**Material quality:** ASTM A351 CF8M

**Connection:** Flange

**Flange finish:** Raised face - 125/250AARH

**Top flange standard:** ISO 5211

**Primary spindle seal material:** PTFE

**Secondary spindle seal material:** FPM (FKM)/PTFE

**Tertiary spindle seal material:** Graphite

**Body seal:** PTFE/Graphite

**Fire safe:** Yes

### Application

- Heavy-duty industrial applications up to 50bar.
- Recommended in: Chemical

### Technical Information

- Flanged connection in accordance with ASME B16.5 RF.
- Floating ball.
- ASME pressure rating: class 300.
- With top-flange in accordance with ISO 5211.
- Media temperature:  $-30/+230^{\circ}\text{C}$ .
- 1/2-inch to 2-inch versions with handle.
- 3" to 10" versions with T-handle.

### Construction

- One-piece housing construction.
- Design in accordance with EN 17292.
- Reduced flow capacity.
- Equipped with antistatic design between ball and housing.
- In accordance with NACE MR0103.
- Construction length in accordance with ASME B16.10.


### Approval

- Fire-safe certified in accordance with ISO 10497 and API 607.
- Fugitive emissions certified according to TA Luft.
- Fugitive emissions certified in accordance with ISO 15848-1, class BH.
- Safety integrity level IEC 61508 SIL3.

### Options

- Equipped with worm gearbox and pneumatic, electric or hydraulic actuators.
- Position feedback for manual or automated valves.
- Stainless-steel extended spindle for insulation (type 7399).
- Other seat materials.

Size table:



DN	d mm	L mm	H mm	M mm	Weight kg
1/2" [15]	11	140	102	180	2
3/4" [20]	14	152	108	180	3.3
1" [25]	19	165	115	180	4.3
1.1/2" [40]	30	190	135	240	9
2" [50]	38	216	142	240	11
3" [80]	62	282	170	600	25.7
4" [100]	76	305	200	350	43.3
6" [150]	100	403	218	600	76.8

Size	Pressure rating	Pressure and temperature range						[°C]
		-30	38	93	149	204	230	
1/2" - 2"	Class 300	50	50	43	34	12	0	[bar]
3" - 8"	Class 300	50	50	35	26	8	0	[bar]

Nominal inner diameter	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Bore	Material ball	Seat material	Spindle material	Actuator material	Article
1/2" [15]	Class 300	ASME B16.10, T2, Serie 8	Handle	F03	Reduced bore	ASTM A351 CF8M	TFM 1600	ASTM A479 316	1.4301	12725821
3/4" [20]	Class 300	ASME B16.10, T2, Serie 8	Handle	F03	Reduced bore	ASTM A351 CF8M	TFM 1600	ASTM A479 316	1.4301	11814369
1" [25]	Class 300	ASME B16.10, T2, Serie 8	Handle	F03	Reduced bore	ASTM A351 CF8M	TFM 1600	ASTM A479 316	1.4301	11814363
1.1/2" [40]	Class 300	ASME B16.10, T2, Serie 8	Handle	F05	Reduced bore	ASTM A351 CF8M	TFM 1600	ASTM A479 316	1.4301	11814370
2" [50]	Class 300	ASME B16.10, T2, Serie 8	Handle	F05	Reduced bore	ASTM A351 CF8M	TFM 1600	ASTM A479 316	1.4301	11814364
3" [80]	Class 300	ASME B16.10, T2, Serie 8	T-wrench	F07	Reduced bore	ASTM A351 CF8M	TFM 1600	ASTM A479 316	Steel, galvanized	11814365
4" [100]	Class 300	ASME B16.10, T2, Serie 8	T-wrench	F10	Reduced bore	ASTM A351 CF8M	TFM 1600	ASTM A479 316	Steel, galvanized	11814366
6" [150]	Class 300	ASME B16.10, T2, Serie 8	T-wrench	F10	Reduced bore	ASTM A351 CF8M	TFM 1600	ASTM A479 316	Steel, galvanized	11814367

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.