



## GF Threaded sleeve in PE-80 Serie: 910 SDR11

### Characteristics

**Series:** 910

**Material:** PE-80

**Connection:** Plastic welded sleeve

**Connection 2:** Internal thread [BSPT]

**Suited for electrofusion fitting:** No

**Minimum medium temperature (continuous):** -20 °C

**Maximum medium temperature (continuous):** 45 °C

Shape	External tube diameter of connection mm	Nominal inner diameter 2	Pressure rating	Article
Transition piece female	20	3/8"	PN10	10047166
Transition piece female	20	1/2"	PN10	10047160
Transition piece female	25	3/4"	PN10	10047161
Transition piece female	32	3/4"	PN10	10047168
Transition piece female	32	1"	PN10	10047162
Transition piece female	40	1"	PN10	10047169
Transition piece female	40	1.1/4"	PN10	10047163
Transition piece female	50	1.1/2"	PN10	10047164
Transition piece female	63	2"	PN10	10047165

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.