



## BLICKLE Castor wheel, series B-ALST

Pressed steel fixed castor, medium duty brackets, with top plate fitting, Heavy duty wheel with Blickle Softhane® polyurethane tread, with aluminium wheel centreBracket: Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.Wheels: Tyre & running tread: Made of high-quality polyurethane-elastomer Blickle Softhane®. Color: green, Shore: 75° Shore AHigh chemical resistance to many aggressive substances. Operating temperature: -25° C to +70° C, temporarily up to +90° C. At ambient temperatures above +40° C the load capacity is reduced. The indicated load capacity refers to applications without obstacles. Maintenance-free under standard conditions.

### Characteristics

**Series:** B-ALST

**Type:** B-ALST 200K

| Wheel model  | Tread material     | Diameter | Width | Bearing weight | Bearing      | Temperature range | Article  |
|--------------|--------------------|----------|-------|----------------|--------------|-------------------|----------|
|              |                    | mm       | mm    | kg             |              | °C                |          |
| Rigid caster | PUR (Polyurethane) | 100      | 40    | 200            | Ball bearing | -25 / 70          | 12533772 |
| Rigid caster | PUR (Polyurethane) | 125      | 40    | 200            | Ball bearing | -25 / 70          | 12533773 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.