


## GF Diaphragm valve Series: 517 PP Push-on flange PN10



### Characteristics

**Series:** 517

**Housing construction:** A (Weir type)

**Housing material:** PP

**Connection:** Push-on flange

**Face to Face norm:** EN 558, Series 1

Membrane material	External tube diameter of connection	Nominal inner diameter	Pressure rating	Face to Face length	Material bonnet	Actuator material	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Article
	mm			mm			°C	°C	
EPDM	20	DN15	PN10	130	PPG	PP	-20	80	12112334
EPDM	25	DN20	PN10	150	PPG	PP	-20	80	12112335
EPDM	32	DN25	PN10	160	PPG	PP	-20	80	12112336
EPDM	32	DN25	PN10	160	PPG	PP	-20	80	12138991
EPDM	40	DN32	PN10	180	PPG	PP	-20	80	12112337
EPDM	50	DN40	PN10	200	PPG	PP	-20	80	12087282
EPDM	63	DN50	PN10	230	PPG	PP	-20	80	12135037
EPDM	63	DN50	PN10	230	PPG	PP	-20	80	12684335
FPM (FKM)	63	DN50	PN10	230	PPG	PP	-20	80	12188288
PTFE	20	DN15	PN10	130	PPG	PP	-20	80	12112309
PTFE	25	DN20	PN10	150	PPG	PP	-20	80	12112310
PTFE	40	DN32	PN10	180	PPG	PP	-20	80	12112313
PTFE	50	DN40	PN10	200	PPG	PP	-20	80	12112314

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.