



## FEMA Pressure switch type DGM

### Characteristics

**Series:** DGM

**Type:** 3783

**Model:** Pressure switch

**Adjustable differential gap:** No

**Process connection:** Internal and external thread (BSPP)

**Size process connection:** 1/4" [8] and 1/2" [15]

**Sensor/feeler type:** Bellows

**Housing material:** Cast aluminium GD-AISI12

**Contact type:** Micro switch

**Switching function:** Change-over

### Application

- Recommended in: Utilities

Adjustment range	Adjustment range pressure unit	Switching differential	Max. pressure bar	Sensor material	Process connection material	Switching power	Electrical connection	Level of protection (IP value)	Ambient temperature °C	Article
0.2 / 1.6	bar	40 mbar	0.8	Copper	Brass	250V AC/8 A res - 250V DC/0.3 A - 24V DC/8 A	Plug EN 175301-803 type A	IP54		10059982
20 / 100	mbar	7 mbar	0.8	Copper	Brass	250V AC/8 A res - 250V DC/0.3 A - 24V DC/8 A	Plug EN 175301-803 type A	IP54		11074574
100 / 600	mbar	25 mbar	2	Copper	Brass	250V AC/8 A res - 250V DC/0.3 A - 24V DC/8 A	Plug EN 175301-803 type A	IP54		10071104
40 / 250	mbar	10 mbar	0.8	Copper	Brass	250V AC/8 A res - 250V DC/0.3 A - 24V DC/8 A	Plug EN 175301-803 type A	IP54		11076347
15 / 60	mbar	6 mbar	0.8	Copper	Brass	250V AC/8 A res - 250V DC/0.3 A - 24V DC/8 A	Plug EN 175301-803 type A	IP54		11072315
15 / 60	mbar	8 mbar	5	Stainless steel 316L	Stainless steel 430	250V AC/8 A res - 250V DC/0.3 A - 24V DC/8 A	Plug EN 175301-803 type A	IP54		11066984
40 / 160	mbar	12 mbar	5	Stainless steel 430	Stainless steel 430	250V AC/3 A res - 250V DC/0.03 A - 24V DC/3 A	Cable entry M16 x 1.5	IP65	-20 / 60	11113116
15 / 60	mbar	8 mbar	5	Stainless steel 430	Stainless steel 430	250V AC/3 A res - 250V DC/0.03 A - 24V DC/3 A	Cable entry M16 x 1.5	IP65	-20 / 60	11250791
100 / 250	mbar	20 mbar	5	Stainless steel 430	Stainless steel 430	250V AC/3 A res - 250V DC/0.03 A - 24V DC/3 A	Cable entry M16 x 1.5	IP65	-20 / 60	11250790
40 / 160	mbar	12 mbar	5	Stainless steel 430	Stainless steel 430	250V AC/8 A res - 250V DC/0.3 A - 24V DC/8 A	Plug EN 175301-803 type A	IP54		11067043

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.