



NORGREN R73G series Excelon pressure reduction valve

- Excelon design allows in-line or modular installation
- Balanced valve design for optimum pressure control
- Standard relieving models allow reduction of downstream pressure when the system is dead-ended
- Push to lock adjusting knob with tamper resistant accessory

Characteristics

Series: Excelon

Type: R73G

Material seal: NBR

Material housing: Aluminium

Temperature range [°C]: -34 / 80 °C

Pressure range bar	Max. inlet pressure bar	Article
0.3 / 10	20	11584853
0.7 / 17	20	11584860
0.3 / 4	20	11584849
0.7 / 17	20	11584858
0.3 / 10	20	11584859
0.7 / 17	20	11584851
0.3 / 10	20	11584856
0.3 / 4	20	11584854
0.3 / 10	20	11584855
0.3 / 10	20	11584850
0.3 / 10	20	11584864
0.3 / 4	20	11584863
0.7 / 17	20	11584868
0.3 / 10	20	11584867
0.3 / 4	20	11584865
0.3 / 10	20	11584866
0.3 / 10	20	11584861
0.3 / 10	20	11584869
0.3 / 10	20	11584870
0.3 / 10	20	11584872
0.3 / 10	20	11584871

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.