



GATES V-Belt Polyurethane profile 3M

Characteristics

Series: Polyflex®

Type: 3M

Height: 2.28 mm

Width (top): 3 mm

Material: PU (Polyurethane)

Tensile Cord: Polyester (PES)

Temperature resistance: -54 / 60 °C

Effective length (ISO) mm	Article
180	839159
185	839140
190	1026326
195	1026327
200	1026328
206	1026329
212	1026330
218	1026331
224	1026332
230	1026333
236	834149
243	1026334
250	1026335
258	1026336
265	1026337
272	824585
280	1026338
290	1026339
300	921289
307	921467
315	833916
325	834262
335	834289
345	1026340
355	841587
365	1026341
375	809470
387	921513
400	921440
412	1026342
425	1026343
437	1026344
450	1026345
462	1026346
475	776661
487	1026347
500	1026348
515	1026349
530	1026350
545	809497

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Effective length (ISO)	Article
mm	
560	834491
580	1026351
600	1026352
615	1026353
630	1026354
650	1026355
670	1026356
690	1026357
710	1026358
730	1026359
750	1026360

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.