

7M

## GATES V-Belt Polyurethane profile 7M

### Characteristics

**Series:** Polyflex®

**Type:** 7M

**Height:** 5.33 mm

**Width (top):** 7 mm

**Material:** PU [Polyurethane]

**Tensile Cord:** Polyester [PES]

**Temperature resistance:** -54 / 60 °C



Effective length (ISO) mm	Article
500	834009
515	1026383
530	1026384
545	1026385
560	835323
580	849170
600	903337
615	1026386
630	835366
650	835374
670	835382
690	958026
710	835412
730	1026387
750	921556
775	932310
800	862843
825	835471
850	835498
875	918415
900	835528
925	835536
950	918407
975	1026388
1030	842834
1060	833347
1090	1026389
1120	835609
1150	835617
1180	835625
1220	835633
1250	1026390
1280	954977
1320	917869
1360	911356
1400	1026391
1450	1026392
1500	835714
1550	1026393
1600	1026394

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Effective length (ISO) mm	Article
1650	862886
1700	1026395
1750	773816
1800	1026396
1850	903345
1900	1026397
1950	1026398
2000	1026399
2060	1026400
2120	1026401
2180	756253
2240	1026402
2300	1026403

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.